TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION

IMPORTANT:
THIS DRAWING SHALL BE USED IN
COMBINATION WITH THE GENERAL
NOTES MD 104.00-01 - MD 104.00-18 AND
STANDARD DETAILS MD 104.01-01 MD 104.01-62

NOTES:


DISTANCES BETWEEN VEHICLES MAY BE INCREASED OR DECREASED DEPENDING ON PAINT DRYING TIME, TERRAIN, LOCAL AREA AND OTHER FACTORS.


FOR STRIPING OPERATIONS IN THE EXTERIOR LANES, USE THE APPROPRIATE RIGHT OR LEFT ARROW ON THE ARROW PANEL. IN THIS CASE, USE THE RIGHT ARROW IF OCCUPYING LANE I AND THE LEFT ARROW IF OCCUPYING LANE 4.

KEY:



ATTENUATOR (TMA)





APPROVAL 9-23-03

REVISED

REVISED

REVISED

APPROVAL

REVISED

REVISED

StateHighway

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

MOBILE MARKING OPERATION/EXP-FREEWAY ALL SPEEDS

STANDARD NO.

MD 104.05-23